



## ROTARY TABLE FOR PACKAGING LINE



### STANDARD ROTATING TABLE

Standard rotary tables built entirely in stainless steel satinated aisi 304.



### ROTATING TABLE CUSTOMIZED

Custom rotary tables made on drawing.



### ACCESSORIES AND SPARE PARTS

Wide range of spare parts always ready in stock.

## INFORMATION

CALL US

**+39 0445 622315**

[www.wellfoodpackaging.com](http://www.wellfoodpackaging.com)  
[info@wellfoodpackaging.com](mailto:info@wellfoodpackaging.com)



Via Fondovilla, 83/C - 36010 Carrè (Italy)  
PHONE: +39 0445 622315 - FAX: +39 0445 1922113  
e-mail: [info@wellfoodpackaging.com](mailto:info@wellfoodpackaging.com)

## ROTATING TABLE STANDARD

Situated at the end of the packaging line they are used as an "Accumulation station" to ease the product unloading stage at packaging machine output and to help the operator in pickup and boxing operations. The end-of-line rotary tables are made completely in stainless steel, with concave or flat trays and mechanical or electronic (inverter) speed variator.

### ROTATING TABLE CONCAVE Ø 1200 / 1400 mm.

- Brushed stainless steel AISI 304.
- Disk rotating concave Ø 1200 / 1400 mm.
- Adjustable rotation speed from 4 > 19 r.p.m. by motovariator.
- Complete control panel with magneto-thermal motor protection and emergency stop switch.
- Height edge of the disc 810 mm. (Standard)
- Adjustable feet + / 40 mm
- Installed power 0,18 Kw. / 0.7 A 380 V 50 Hz
- Manufactured in compliance with CE regulations.



### ROTATING TABLE CONCAVE FOR HEAVY PRODUCTS Ø 1200 / 1400 mm.

- Brushed stainless steel AISI 304.
- Disk rotating concave Ø 1200 / 1400 mm.
- Adjustable rotation speed from 4 > 19 r.p.m. by motovariator.
- Complete control panel with magneto-thermal motor protection and emergency stop switch.
- Height edge of the disc 810 mm. (Standard)
- Adjustable feet + / 40 mm
- Installed power 0,18 Kw. / 0.7 A 380 V 50 Hz
- Manufactured in compliance with CE regulations.



### ROTATING TABLE CONVEX Ø 1200 / 1400 mm.

- Brushed stainless steel AISI 304.
- Disk rotating convex Ø 1200 / 1400 mm.
- Adjustable rotation speed from 4 > 19 r.p.m. by motovariator.
- Complete control panel with magneto-thermal motor protection and emergency stop switch.
- Height edge of the disc 810 mm. (Standard)
- Adjustable feet + / 40 mm
- Installed power 0,18 Kw. / 0.7 A 380 V 50 Hz
- Manufactured in compliance with CE regulations.



## ROTATING TABLE STANDARD

Positioned in the entrance of the conveyor belt, or directly to the machine to be fed, it has the function of "station of accumulation and distribution". The products can be loaded manually or by conveyor belt. The adjustable deflectors help to sort and align products for food evenly and without interruption the machine.

Positioned in the conveyor belt or output of a packaging machine, filling machine, labeling etc., Works from the collection and accumulation products. The rotary tables have a variable speed drive. The rotating disc may be provided in a slippery plastic material or stainless steel.

### ROTARY TABLE IN SLIPPERY PLASTIC MATERIAL Ø 1200 / 1400 mm.

- Brushed stainless steel AISI 304.
- Disk rotating plain Ø 1200 / 1400 mm.
- Adjustable rotation speed from 4 > 19 r.p.m. by motovariator.
- Complete control panel with magneto-thermal motor protection and emergency stop switch.
- Height edge of the disc 810 mm. (Standard)
- Adjustable feet + / 40 mm
- Installed power 0,18 Kw. / 0.7 A 380 V 50 Hz
- Manufactured in compliance with CE regulations.



### ROTARY TABLE WITH SIDE FOR HEAVY PRODUCTS Ø 1200 / 1400 mm.

- Brushed stainless steel AISI 304.
- Disk rotating plain Ø 1200 / 1400 mm.
- Bank of a rod containment
- Adjustable rotation speed from 4 > 19 r.p.m. by motovariator.
- Complete control panel with magneto-thermal motor protection and emergency stop switch.
- Height edge of the disc 810 mm. (Standard)
- Adjustable feet + / 40 mm
- Installed power 0,18 Kw. / 0.7 A 380 V 50 Hz
- Manufactured in compliance with CE regulations.



### ROTARY TABLE "CUP" Ø 1060 mm.

- Brushed stainless steel AISI 304.
- Disk rotating concave Ø 1060 mm.
- Adjustable rotation speed from 4 > 19 r.p.m. by motovariator.
- Complete control panel with magneto-thermal motor protection and emergency stop switch.
- Height edge of the disc 810 mm. (Standard)
- Adjustable feet + / 40 mm
- Installed power 0,18 Kw. / 0.7 A 380 V 50 Hz
- Manufactured in compliance with CE regulations.



## ROTATING TABLE CUSTOMIZED



Ø 1800 mm  
with banks



Ø 1200 mm  
with banks



Ø 1800 mm  
with banks



Ø 600 mm  
liquid discharge



Ø 1200 mm  
with banks



Ø 1200 mm  
loading &  
unloading



Ø 1200 mm  
with banks

## ACCESSORIES & SPARE PARTS



Electric motor



Control panel



Adjustable feet



Wheels with brake

## Optional

- Disk in slippery material or inox
- Pivoting wheels in stainless steel with brake
- Height on request
- Adjustable diverter inbound products
- Adjustable diverter output products
- Diverter system and output product alignment
- Double containment ring
- Closed edge height 50 mm.
- Incoming product loading plan
- Slide inbound and outbound products

## Certification CE



## User manual



# Wellfood

Food packaging equipment

## INFORMATION

CALL OR WRITE US

**+39 0445 622315**

[www.wellfoodpackaging.com](http://www.wellfoodpackaging.com)  
[info@wellfoodpackaging.com](mailto:info@wellfoodpackaging.com)

## WELLFOOD

Via Fondovilla, 84/C - 36010 CARRE' (VI) Italy  
Phone: +39 0445 622315 Fax: +39 0445 1922113  
[www.wellfoodpackaging.com](http://www.wellfoodpackaging.com) - [info@wellfoodpackaging.com](mailto:info@wellfoodpackaging.com)